
Extension of Photonic Processor Arithmetic and Architecture

Author: L'Architech (Gabriel Breton-Breault)

Date: August 2026

Language: English (translated from French)

Introduction

This document presents the complete extension of the arithmetic used in the photonic processor, as well as the architectural principles that enable the execution of directional calculations based on light. Unlike electronic processors, which rely on fixed binary registers and specialized circuits for each operation, the photonic processor uses a unified optical mechanism: splitting light and assembling light.

All mathematical operations — addition, subtraction, multiplication, division, and exponential structures of the type n^n^n — are produced by the same light transformations. Light never changes its behavior: it splits, recombines, densifies, or reduces. What changes is the interpretation given by the read/write head of the quartz block, which determines whether an optical transformation corresponds to an addition, a multiplication, a division, a subtraction, or exponential growth.

This architecture enables unbounded arithmetic, where numbers are not stored but described by compact directional structures. Extreme values, such as exponential towers n^n^n , can be represented without depending on a fixed binary format, thanks to the ability of photonic quartz to manipulate light as a mathematical operator.

This document details the internal mechanisms, optical operations, directional structures, and parallel computation principles that define photonic arithmetic.

Section 1 — Fundamental Optical Properties of the Photonic Processor

1.1. Optical Nature of Computation

The photonic processor relies on a computation mechanism entirely based on light. Unlike electronic architectures, where each operation depends on a specialized circuit, the photonic processor uses a single raw material: the light beam. All mathematical operations — addition, subtraction, multiplication, division, exponential divisions, and structures of the type $n^n n^n n^n$ — are carried out using the same optical transformations.

Light is manipulated according to four fundamental properties:

- intensity,
- direction,
- phase,
- density.

These properties constitute the physical foundation of photonic arithmetic.

1.2. Physical Dimensions of the Photonic Processor

The photonic processor is a 12 cm cube, entirely printed in pure silica. Between the silica structures lies a non-photosensitive polymer, whose role is to mechanically stabilize the optical network without interfering with light.

The internal optical network is printed in three dimensions and allows light to travel in 17 distinct directions:

In the X-Y plane (horizontal layer)

Light can travel:

- toward the North,
- toward the South,
- toward the East,
- toward the West,
- and in the 4 diagonals of the X-Y plane.

Along the Z axis (vertical)

Light can travel:

- in a straight line toward the upper layer,
- or in the 8 vertical diagonals, corresponding to the same directions as in the X-Y plane, but tilted upward.

Total: 17 optical directions — This three-dimensional network allows the photonic processor to execute complex directional computations, using light as a mathematical structure.

1.3. Internal Prisms for Splitting and Recombining Light

Inside the processor, micro-prisms are printed directly into the silica. These prisms are the physical elements responsible for:

- splitting light into multiple beams,
- recombining light into a single beam.

They enable:

- multidirectional splittings,
- geometric recombinations,
- optical densifications,
- fractal distributions,
- and exponential divisions, where a beam is split according to a repeated directional pattern, producing structures of the type n^n but applied to division.

These prisms are essential: they physically carry out the transformations that the read/write head subsequently interprets as mathematical operations.

1.4. Division and Assembly of Light

The photonic processor is designed to execute two essential physical actions:

1. Division of Light

A beam can be split into multiple sub-beams. This splitting can represent:

- a division,
- an exponential division,
- an extraction,
- a directional reduction,
- or an exponential structure when the splitting is repeated according to a $n^n n^n$ pattern.

2. Assembly of Light

Multiple beams can be recombined into one. This recombination can represent:

- an addition,
- a multiplication,
- an amplification,
- or exponential growth, depending on how the beams densify.

These two actions — splitting and assembling — are the only physical operations required. Everything else is a matter of interpretation.

1.5. Interpretation by the Read/Write Head

The read/write head of the quartz block analyzes:

- the direction of the beam,
- its density,
- its phase,
- its polarity,
- its color,
- its internal pattern.

It then determines whether the light transformation corresponds to:

- an addition,
- a subtraction,
- a multiplication,

- a division,
- an exponential division,
- or an exponential structure of the type n^{nnn} .

Light executes the transformation. The read/write head gives the mathematical meaning.

1.6. Unification of Mathematical Operations

In electronic architectures, each operation has:

- a dedicated circuit,
- a specific instruction,
- a distinct physical behavior.

In the photonic processor:

- a single physical mechanism (division and assembly),
- multiple possible interpretations,
- determined by the read/write head.

Thus:

- a splitting can be a division, an exponential division, or a n^{nnn} ,
- a recombination can be an addition or a multiplication,
- an amplification can be a multiplication or an exponential,
- a reduction can be a subtraction or a directional extraction.

Operations are not circuits: they are optical interpretations.

1.7. Consequence: Extensible and Unbounded Arithmetic

Because light can be split and assembled without theoretical limit, and because the read/write head can interpret these transformations according to directional structures, photonic arithmetic enables the representation of extreme numbers, including:

- exponential towers n^{nnn} ,
- exponential divisions,
- numerical fractals,

- directional cycles,
- compressed structures.

Numerical representation is not stored: it is described by light.

1.8. Conclusion of Section 1

The fundamental optical properties of the photonic processor rest on a simple yet universal mechanism: splitting light and assembling it. Combined with a three-dimensional optical network printed in pure silica, stabilized by a non-photosensitive polymer, equipped with internal prisms, and capable of 17 propagation directions, they enable unbounded arithmetic, including exponential divisions and n^n structures.

Section 2 — Role and Architecture of the Quartz Read/Write Heads (the Scorpions)

2.1. General Function of the Scorpions

The two read/write heads of the quartz cube are called the **Scorpions**. This name designates the bilateral assembly that allows the photonic processor to:

- read binary data from the quartz disk,
- interpret it,
- convert it into directional light,
- transmit the light to the photonic processor,
- receive the transformed light,
- reconvert it into binary data for the rest of the system.

The Scorpions are the optical interpreters of the system: they transform binary logic into light logic.

2.2. The Quartz Disk: Binary Storage and Program Logic

The quartz disk is entirely engraved in binary. It contains:

- the complete program logic,
- control structures,
- variables,
- instructions,
- computation tables,
- pre-compiled directional structures.

The disk contains no photonic logic. It stores only binary data. The Scorpions:

- read this data,
- interpret its meaning,
- convert it into directional light beams,
- inject these beams into the photonic processor.

➤ *The quartz disk contains the program logic.*

➤ *The Scorpions transform this logic into light.*

➤ *The photonic processor executes the light.*

2.3. Physical Connection Between the Scorpions and the Photonic Processor

The 12 cm cube photonic processor is printed directly onto the motherboard. The lower face of the cube is divided into two zones:

Zone	Dimensions	Function
Zone 1 — Light Input	6 cm × 12 cm	The Scorpions' lasers inject light into this zone.
Zone 2 — Light Output	6 cm × 12 cm	The Scorpions' sensors retrieve the transformed light.

Between these two zones, an optical network printed on the motherboard ensures the connection between injection lasers, output sensors, and the two Scorpions. This network consists of:

- pure silica,
- a non-photosensitive polymer that mechanically stabilizes the optical structures.

This network is aligned with the 17 internal directions of the photonic processor.

2.4. The 10 cm Quartz Cube: Capacity and Role

The Scorpions are mounted on a 10 cm quartz cube, which serves as the optical read/write unit. The quartz can stabilize:

- directional peta-fractals,
- exponential $n^n n^n$ structures,
- exponential divisions,
- complex directional cycles,
- compressed optical patterns.

Its capacity is not measured in bits, but in maximum optical density.

2.5. Bilateral Architecture: The Two Scorpions

The Scorpions are placed on two opposite faces of the quartz cube:

- **Scorpion A:** front face
- **Scorpion B:** rear face

This bilateral architecture enables:

- doubled read/write surface area,
- multiplied optical throughput,
- faster directional interpretation,
- simultaneous stabilization of light structures.

The two Scorpions can:

- read simultaneously,
- write simultaneously,
- read on one side and write on the other,
- stabilize two optical structures in parallel.

2.6. Full X-Y Surface Coverage

The Scorpions do not move. They are fixed, but cover 100% of the quartz X-Y surface thanks to:

- optical sensor matrices,
- directional micro-lenses,
- phase detectors,
- density detectors,
- polarity detectors.

Every point on the quartz surface is accessible without mechanical movement. This eliminates:

- movement delays,
- positioning errors,
- precision losses.

Data throughput is thus maximized, as the entire surface is permanently active.

2.7. Communication with Other Computer Components

The Scorpions are also the primary interface between the photonic processor and the rest of the computing system. They communicate directly with:

- the graphics card,
- the network card,
- the sound card,
- storage controllers,
- communication buses,
- external interfaces.

They convert:

- binary data from the system → light for the processor,
- light from the processor → binary data for other components.

➤ *The Scorpions are the bridge between the photonic world and the electronic world.*

2.8. Conclusion of Section 2

The two bilateral read/write heads of the quartz cube, called the Scorpions, constitute the master interface between the binary world of the quartz disk and the photonic world of the processor. Their name comes from their functional form: each one grips the quartz cube by an edge, like the claws of a scorpion, while their optical inputs and outputs, located at the rear of each head, evoke the articulated tail of a scorpion, through which the light beams transit.

Fixed yet covering 100% of the X-Y surface of the quartz, the Scorpions simultaneously read binary data, interpret it, convert it into directional light, and retrieve the transformed light to reconvert it into electronic data. Their bilateral architecture doubles the active surface, increases optical throughput, stabilizes directional structures, and allows the photonic processor to execute unbounded arithmetic including exponential divisions and n^n structures.

Thanks to their direct connection to the optical network printed in pure silica, and their role as a gateway to other computer components (graphics card, network card, sound card, storage controllers), the Scorpions ensure total coherence between photonic computation and the electronic environment. They are the interpreters, translators, and stabilizers of the system: the two claws and the tail of the scorpion that breathe life into the photonic processor.

Section 3 — Unbounded Numerical Representation

3.1. General Principle of Numerical Representation

In this system, numerical representation does not rely exclusively on traditional binary storage. Values can be recorded on the quartz disk when the program requires it, but the internal representation used by the photonic processor is based on directional light structures. Thus, a number can exist in two forms:

- **Binary form:** stored on the quartz disk when necessary.
- **Photonic form:** represented by an unbounded optical structure manipulated directly by the processor.

This duality allows the stability of binary storage to be combined with the unlimited computational capacity of light.

3.2. Role of the Quartz Disk in Managing Numerical Values

The quartz disk is engraved in binary and contains:

- initial numerical values,
- constants,
- variables,
- intermediate results when the program requests them,
- output data,
- control structures,
- the complete program logic.

The disk stores no directional structures. Numerical values are recorded on it only when a program needs to retain or reuse them. Once read, they are converted into light by the read/write heads (the Scorpions) and transmitted to the photonic processor.

3.3. Directional Structures as Numerical Representation

Once converted into light, a number becomes a directional structure. This structure can be defined by:

- a light density,
- a phase,
- a polarity,
- an orientation,
- a splitting,
- a recombination,
- a fractal pattern,
- an amplification.

Each directional structure is self-contained: it holds its own internal definition and does not depend on a fixed numerical format. The photonic processor reads and manipulates these structures directly, without intermediate conversion.

3.4. Representation of Extreme Exponential Structures

Exponential structures of the type $n^n n$ are represented by optical patterns that are:

- densified,
- fractalized,
- multi-layered,
- multi-split,
- amplified.

These structures cannot be efficiently stored in decimal or classical binary. They are therefore represented exclusively in directional form, which allows extreme values to be manipulated without theoretical limit.

3.5. Storage of Exponential Levels in Exponent Form

When a program requires the execution of an exponential structure, the quartz disk never records the number of levels in decimal form. Instead of storing an exponentiation height such as:

- 3 levels,
- 12 levels,
- 245 levels,

the disk directly records the exponent structure itself, for example:

- $n^n n$,
- $n^n n^n$,
- or any other equivalent directional form.

This method offers several advantages:

- no decimal conversion,
- maximum information compression,
- direct coherence with photonic representation,
- compatibility with unbounded structures,
- immediate interpretation by the Scorpions,

- reduced storage cost.

The exponential level is thus stored in its operational form, not in a decimal numerical representation.

3.6. Directional Compression

Numerical structures can be compressed through:

- optical cycles,
- directional fractals,
- modulated densities,
- repetitive patterns.

An extremely large value can be compressed into:

- a single direction,
- a single phase,
- a single density.

The photonic processor can then deploy or expand this structure according to the needs of the calculation.

3.7. Dynamic Representation

Numerical representation is dynamic. During computation, light can:

- change direction,
- modify its density,
- adjust its phase,
- split,
- recombine,
- fractalize.

Each transformation modifies the numerical value represented. Computation thus becomes a continuous transformation of the light structure.

3.8. Advantages of Unbounded Representation

1. **Binary storage when necessary** — Values can be preserved in a stable manner.
2. **Unlimited photonic representation** — Light has no fixed format.
3. **No overflow** — Light reorganizes rather than saturates.
4. **Continuous precision** — Optical density is not discrete.
5. **Compact fractal structures** — Extreme values are compressed.
6. **Geometric directional structures** — Numbers become optical objects.
7. **Dynamic evolution** — Values transform during computation.

3.9. Conclusion of Section 3

Unbounded numerical representation rests on a fundamental duality: values can be stored in binary on the quartz disk when the program requires it, but their internal representation is provided by directional light structures manipulated directly by the photonic processor. Exponential levels are recorded in exponent form rather than in decimal, guaranteeing total coherence between storage and computation. Thanks to optical fractals, directional cycles, exponential splittings, and n^n structures, this system enables the manipulation of values of a magnitude inaccessible to traditional electronic architectures.

Section 4 — Definition of Mathematical Operations

4.1. General Principle of Optical Operations

Mathematical operations are not executed by electronic circuits, but by light transformations internal to the photonic processor. These transformations rely on two fundamental physical mechanisms:

- the division of light,
- the assembly of light.

Combined with the 17 internal optical directions, these actions enable the definition of all mathematical operations, including extreme structures such as n^{nnn} .

4.2. Addition

Addition corresponds to the assembly of two light beams in the same direction, producing a resulting optical density equal to the sum of the initial densities.

4.3. Subtraction

Subtraction is achieved by extracting a portion of the luminous density from a beam, while preserving its direction.

4.4. Multiplication

Multiplication is obtained by light amplification, resulting from the recombination of several identical beams.

4.5. Division

Division is achieved by splitting a beam into several sub-beams of equal density.

4.6. Exponential Division

Optical definition

Exponential division is a repeated splitting, where each sub-beam is itself split according to a recurring directional pattern. This structure produces fractal distributions of luminous density.

Mathematical capacity

Exponential division enables the execution of:

- the square of a number,
- the cube of a number,
- powers of higher dimensions,
- multi-level geometric computations,
- complex directional structures.

Exponential division applied to a sphere

Exponential division can also be applied to a spherical structure. In this case, each light splitting divides the directional space available inside the sphere:

8. The first level divides the sphere into a set of primary directions.
9. The second level subdivides each of these directions into sub-directions.

10. The third level further subdivides each sub-direction, and so on.

This process continues until the internal space is saturated, that is, until:

- all possible directions from the center of the sphere are represented,
- no additional subdivision can create a new direction,
- directional density reaches its geometric maximum.

Scientific result

Exponential division thus allows the computation of the total number of possible directions from the center of a sphere, by subdividing the directional space to its maximum threshold. This computation is impossible to achieve electronically, but becomes trivial in a photonic architecture where light can split into directional fractal patterns.

4.7. Exponentiation

Exponentiation is achieved by fractal amplification, where a beam is densified according to a repeated directional pattern. It produces extreme optical structures such as n^{nnn} .

4.8. Directional Operations

Some operations are geometric rather than numerical:

- directional rotation,
- optical translation,
- fractal compression,
- directional deployment,
- polarity inversion,
- optical reflection.

4.9. Combined Operations

The system also enables hybrid operations, such as:

- addition + amplification,
- division + exponential splitting,
- multiplication + fractalization,

- exponentiation + directional compression.

4.10. Conclusion of Section 4

The mathematical operations of the photonic processor are defined by internal light transformations, interpreted by the read/write heads. Exponential division plays a central role: it allows not only the computation of geometric powers (squares, cubes, higher dimensions), but also the division of the directional space of a sphere to saturation, in order to determine the total number of possible directions from a central point. Extreme structures of the $n^n n$ type are produced by directional fractal patterns, enabling unbounded and entirely optical arithmetic.

Section 5 — Exponential Structures $n^n n$

5.1. General Definition of Exponential Structures

Exponential structures of the $n^n n$ type represent extreme mathematical forms, impossible to manipulate in a classical electronic architecture. In this system, these structures are not stored in decimal or binary form: they are represented by fractal light patterns, built by repeated directional amplification.

An exponential structure is defined by:

- an exponent level,
- a directional repetition,
- a growing optical density,
- a fractal geometry,
- a multi-layer amplification.

These structures are manipulated directly by the photonic processor.

5.2. Optical Construction of an Exponential Structure

The construction of an exponential structure relies on a repetitive optical process:

11. **Initial amplification** — A light beam is densified in a given direction.
12. **Secondary amplification** — The amplified beam is itself amplified in a new direction.
13. **Tertiary amplification** — The process repeats, creating a multi-level structure.
14. **Fractal amplification** — Each amplified level becomes a fractal pattern, reproduced in multiple directions.
15. **Total amplification** — The structure reaches an optical form equivalent to n^{nnnn} .

Each level is defined by an exponent structure, never by a decimal number.

5.3. Directional Representation of Exponential Structures

Exponential structures are represented by directional patterns. Each level of exponentiation corresponds to an additional directional layer. Conceptual example:

Notation	Directional Description
n	One direction
n^n	A direction amplified by a second direction
$n^n n$	A three-level directional structure
$n^n n^n$	A four-level fractal structure
$n^n n^n n$	A saturated five-level structure

Light encodes these structures through:

- density,
- phase,
- polarity,
- internal geometry,
- fractal repetition.

5.4. Directional Saturation in a Sphere

Exponential structures can be applied to a spherical geometry. In this case, each level of exponentiation subdivides the internal directional space of the sphere.

Saturation process:

16. **Primary division** — The sphere is divided into main directions.
17. **Secondary division** — Each main direction is subdivided into sub-directions.
18. **Tertiary division** — Each sub-direction is further subdivided.
19. **Exponential division** — The process repeats according to a fractal pattern until saturation.

Saturation of internal space

Saturation is reached when:

- no new direction can be created,
- directional density reaches its geometric maximum,
- the internal structure of the sphere is fully subdivided.

Scientific result

The exponential structure enables the computation of the total number of possible directions from the center of a sphere, by subdividing the directional space to its maximum threshold. This computation is impossible to achieve electronically, but becomes feasible in a photonic architecture where light can split and amplify according to fractal patterns.

5.5. Multidimensional Exponential Structures

Exponential structures are not limited to linear or spherical geometry. They can be applied to:

- hyperspheres,
- complex directional volumes,
- three-dimensional fractal geometries,
- multi-dimensional optical spaces.

Each additional dimension adds a level of exponentiation, enabling the representation of structures of extreme magnitude.

5.6. Optical Manipulation of Exponential Structures

The photonic processor manipulates exponential structures through:

- fractal amplification,
- directional recombination,

- exponential splitting,
- directional compression,
- optical deployment.

The Scorpions interpret these transformations as:

- exponentiations,
- exponential divisions,
- geometric powers,
- multi-level structures.

5.7. Advantages of Optical Exponential Structures

- 20. **Unbounded representation** — Structures have no numerical limit.
- 21. **Extreme compression** — A gigantic structure can be compressed into a single direction.
- 22. **Geometric manipulation** — Structures are optical objects, not numbers.
- 23. **Multidimensional computation** — Exponentiations can represent directional volumes.
- 24. **Directional saturation** — The system can compute the maximum number of directions within a sphere.
- 25. **Full compatibility with exponential division** — Exponential structures and exponential divisions are complementary.

5.8. Conclusion of Section 5

Exponential structures of the $n^n n$ type constitute one of the foundations of photonic arithmetic. They are represented by fractal light patterns, built by repeated directional amplification, and enable the manipulation of values of a magnitude inaccessible to electronic architectures. Applied to a sphere, they allow the directional space to be subdivided until saturation and the total number of possible directions from a central point to be determined. These structures are manipulated directly by the photonic processor, offering unbounded, multidimensional, and entirely optical arithmetic.

General Conclusion

This photonic system proposes a computation architecture founded on light, in which mathematical operations, numerical structures, and multidimensional representations are defined by optical transformations rather than electronic instructions. Values can be stored in binary when necessary, but their operational form is always directional, fractal, or geometric, enabling unbounded arithmetic.

Exponential divisions, capable of subdividing a directional volume until saturation, offer a means of computing geometric powers such as squares, cubes, and higher dimensions. Exponential structures of the n^n type are represented by multi-level light patterns, whose stability is ensured by the internal optical environment of the processor. The read/write heads interpret these structures directly, guaranteeing perfect continuity between binary storage, photonic representation, and the execution of computations.

By combining splitting, amplification, fractalization, and directional organization, this system enables the manipulation of values and geometries impossible to represent electronically. It thus establishes a theoretical basis for entirely optical computing, capable of processing extreme structures, saturated volumes, and multidimensional computations with total internal coherence.